

## Informationen zum Produkt



## 190D

### Weitere Füllvolumen Ø 69mm:

80ml  
120ml  
155ml  
155ml mit Henkel  
190ml



Füllvolumen:	Ø:	Höhe m.D.:	Gewicht Becher, Deckel (+/-3%)	IML-Druck Becher	IML-Druck Deckel	Weiteres:
190ml	69mm	84,4mm	8,40g / 1,85g	nein	ja	Siehe Spez.
<ul style="list-style-type: none"> <li>• PP-Spritzgussbecher mit Originalitätsverschluss (BRC-Zertifikat Lebensmittelsicherheit)</li> <li>• Standardausführung: klar mit klarem Deckel (Einfärbung in Standardfarben möglich)</li> <li>• Fertigung in Tiefkühlqualität zur Erhöhung der Schlagfähigkeit auf Anfrage (Eisindustrie)</li> </ul>						
Menge je Palette:	in 20 Kombiboxen paarig gep.	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Palette	Paletten-Höhe	Weiteres:
20.880 St.	1.044 St.	592x392x400mm 720g	28g	1200x800x150mm 23kg	Inkl. Pal. 2,20m	Siehe Spez.

## Standardfarben zur Einfärbung



**schwarz**



**rot**



**braun**



**weiss**



**orange**



**gelb**



**grün**



**blau**



**dunkelblau**

## Technical Data Sheet

### Container 190ml Ø67, lid H

<b>1. Dimensions</b>	Shape:	Round
	Volume under lid:	190 ml
	External diameter top (with lid):	68,84 mm
	External diameter bottom:	52,6 mm
	Height (with lid):	84,4 mm
<b>2. Closure system</b>	Closure type:	Snap-On
	Protective collar:	Yes
	Tamper evident:	Yes
	Lid type options:	Standard lid
<b>3. Weight*</b>	Container:	8,40 g
	Lid:	1,85 g
	*the weight can have +/-3 % error	
<b>4. Handle</b>	Handle available:	No
<b>5. Raw material</b>	Raw material:	PP
	Masterbatch colours:	Standard colours or colours coordinated according to customer's presented colour pallet or sample.
	Approvals:	All raw materials and masterbatches used in the production process have the appropriate food contact approvals.
<b>6. Decoration</b>	IML decoration (container):	No
	IML decoration (lid):	Yes
<b>7. Other characteristic</b>	Uses:	Containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.
	Hot filling:	Packaging is suitable for contact with the hot filling (85 ° C - 95 ° C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before approval for use at hot temperatures.
	Cold temperatures:	Package made from the special cold-resistant material can be used at temperatures below -20 °C . It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before approval for use at low temperatures.
	Storage:	Suitable storage include protection of direct sun light, rain, very high temperatures over a long period. Package must be not more than 2.4 m in height and at least 1 m away from the heat source. Recommended period of storage - 12 months after delivery to suitable storage.
<b>8. Packing</b>	<b>Standard</b>	
	Containers per carton box	1248 pcs.
	Lids per carton box	5760 pcs.
	Containers and lids packed together per carton box	1044 pcs.
	Carton boxes per pallet	20 pcs.
	Containers per pallet	24960 pcs.
	Lids per pallet	115200 pcs.
	Containers and lids packed together per pallet	20880 pcs.
	Height including pallet	2,2 m
	<b>Optional</b>	
	Carton boxes per pallet	24 pcs.
	Containers per pallet	29952 pcs.
	Lids per pallet	138240 pcs.
	Containers and lids packed together per pallet	25056 pcs.
	Height including pallet	2,6 m

